

Robert Abbey, Inc.

ASSEMBLY INSTRUCTIONS FOR YOUR

WINSTON 6-LIGHT CHANDELIER

Warning: *If any special control devices are used with this fixture, follow the instructions carefully to assure full compliance with N.E.C. requirements. If there are any questions, contact a qualified electrical contractor.*

ASSEMBLY INSTRUCTIONS

1. SHUT OFF THE MAIN ELECTRICAL SUPPLY FROM THE MAIN FUSE BOX / CIRCUIT BREAKER.
2. Remove all parts from carton, and place on a soft surface.
3. Affix crossbar (A) to "J BOX" using screws (C) provided.
4. Affix the extension arms (O) to the dummy canopy (I) by inserting upper hook (K) into corresponding canopy loop (J). Insert lower hook (M) into loop (N). Repeat until all extension arms are installed.
5. After all extension arms are installed, thread safety screws (L) into upper hook (K) until hand tight.
6. Measure desired drop for fixture to hang and add / remove chain links (G) accordingly. Chain break tool required. (not included)
7. Attach quick link (H) to bottom loop of chain (G). Lift fixture and attach loop on top of dummy canopy (I) to quick link (H). Close opening in quick link (H) to secure fixture. Guide wiring through chain links (G) and center hole in canopy (D).
8. Thread collar (E) down hang straight (F) and slide down chain links (H) to rest on bottom link.
9. Slide center hole of canopy (D) down hang straight (F) and chain links (G) to rest on bottom chain link.
10. Holding fixture by hang straight (F), lift fixture to threaded nipple (B). Guide wiring through center hole in threaded nipple (B). Pull wiring until hang straight (F) and threaded nipple (B) are touching. Thread hang straight (F) onto threaded nipple (B).
11. Make proper electrical connection. A licensed electrician is recommended.
12. Connect the ground wire (silver) from the fixture to the ground wire in the outlet box (copper, green, or silver). Connect the black wire from fixture (or smooth side of wire) to black wire in outlet box using wire nuts (provided). Connect white wire from fixture (or rough side of wire) to the white wire in the outlet box using wire nuts (provided).
13. Hold canopy (D) tightly against the ceiling. Thread collar (E) up hang straight (F) to secure position of canopy (D).
14. Install six (6) Type B, 60 watt maximum light bulbs into sockets (Q).
15. Open shade clip (located inside shade (P)) and gently slide down onto light bulb. Repeat step for each shade.

